

**DECLARATION OF PERFORMANCE**

**N. 119-CPR-24-05**

1. Unique identification code of the product-type: **Calcio Ossido Macinato HQ CL-90-Q (R5 - P1)**
2. Intended uses: **Building lime used as binder for mortar, other construction products, and civil engineering applications**
3. Manufacturer: **FASSA S.r.l. - Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY - [www.fassabortolo.it](http://www.fassabortolo.it)**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **2+**
6. Harmonised standard: **EN 459-1:2010**

Notified bodies: **ICMQ (n.1305)**

7. Declared performances:

Costituents	<b>CaO + MgO: ≥ 90%</b> <b>MgO: ≤ 5 %</b> <b>CO2: ≤ 4 %</b> <b>SO3: ≤ 2 %</b>	Grain Size (Residue by mass)	<b>P1</b>
Available Lime	≥ 80 %	Penetration	<b>NPD</b>
Soundness	<b>Pass</b>	Durability	<b>NPD</b>
Reactivity	<b>R5</b>	Dangerous substances	<b>See MSDS</b>

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Dott. Roberto Moreschi**

Lime Division - Research and Development Manager

Spresiano (TV), 06/05/2024

Calcio Ossido Macinato HQ CL-90-Q (R5 - P1)



1305

**Fassa s.r.l.**

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

**Plant:**

**Via Leonino da Zara, 60 - 25018 Montichiari (BS)**

**Via Lago di Alleghe, 45 - 36015 Schio (VI)**

17

**119-CPR-24-05**

**EN 459-1:2010**

**Calcio Ossido Macinato HQ CL-90-Q (R5 - P1)**

Building lime used as binder for mortar, other construction products, and civil engineering applications

The declared performance by levels or classes is defined by the building lime designation