

DECLARATION OF PERFORMANCE

N. 102-CPR-24-09

1. Unique identification code of the product-type: **FASSASOIL 102 CL-90-Q (R5 - Psv)**
2. Intended uses: **Building lime used as binder for mortar, other construction products, and civil engineering applications**
3. Manufacturer: **FASSA S.r.l. - Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY - www.fassabortolo.it**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **2+**
6. Harmonised standard: **EN 459-1:2010**

Notified bodies: **ICMQ (n.1305)**

7. Declared performances:

Constituents	CaO + MgO: ≥ 90% MgO: ≤ 5 % CO₂: ≤ 4 % SO₃: ≤ 2 %	Grain Size (Residue by mass)	Psv
Available Lime	≥ 80 %	Penetration	NPD
Soundness	Pass	Durability	NPD
Reactivity	R5	Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Roberto Moreschi

Lime Division - Research and Development Manager

Spresiano (TV), 11/09/2024

FASSASOIL 102 CL-90-Q (R5 - Psv)



1305

Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

Plant:

Via Fornaci, 8 - 31027 Spresiano (TV)

Via Leonino da Zara, 60 - 25018 Montichiari (BS)

Località Soman, 2597/B - 37020 Ceraino di Dolcè (VR)

03

102-CPR-24-09

EN 459-1:2010

FASSASOIL 102 CL-90-Q (R5 - Psv)

Building lime used as binder for mortar, other construction products, and civil engineering applications

The declared performance by levels or classes is defined by the building lime designation